

DOOSAN

DL450-5 WHEEL LOADER

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- Standard Z-Bar (High Lift Z-Bar Available)
- Limited Slip Differentials
- Selectable Work Modes (Eco, Normal & Power)
- Separate Cooling and Engine Compartments, Variable Speed Reversing Cooling Fan, Exhaust Heat Exchanger
- Telematics — 3 Year Subscription
- Options — Hydraulic Locking Front & Conventional Rear Differential, Axle Oil Cooler, Emergency Steer, 5 Gear with Lock-up Clutch, Hydraulic Load Isolation System, Finger Tip Three Lever Controls, Electric Joystick Steering, Rotating Beacon, Rear View Camera, 110 Volt Plug Heater, Auto Greasing System, Rubber Fender Protectors, Full Fender with Rubber Protector

NEW MODEL OVERVIEW	DL450-5
Rated Power – Gross (HP per SAE J1995)	345 hp (257 kW) @ 1800 rpm
Operating Weight	56,868 lb. (25 795 kg)
Static Tipping Load (Straight)	45,228 lb. (20 515 kg)
Static Tipping Load (Full Turn)	39,937 lb. (18 115 kg)
Maximum Dumping Height	10' 8" (3240 mm)
Bucket Capacity Heaped	6.3 yd ³ (4.8 m ³)
Bucket Hinge Pin Height	14' 9" (4500 mm)
Breakout Force	51,930 lbf. (23 555 kgf)
Maximum Dump (Reach @ full height)	4' 2" (1280 mm)
External Radius, Bucket Edge	23' 6" (7160 mm)

PL-1009-0414

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DL450-3.