

DOOSAN

DL300-5 WHEEL LOADER

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- Standard Z-Bar (High Lift Z-Bar Available)
- Limited Slip Differentials
- Selectabel Work Modes (Eco, Normal & Power)
- Separate Cooling and Engine Compartments, Variable Speed Reversing Cooling Fan, Exhaust Heat Exchanger
- Telematics — 3 Year Subscription
- Options — Hydraulic Locking Front & Conventional Rear Deifferential, Emergency Steer, 5 Gear with Lock-up Clutch, Hydraulic Load Isolation System, Finger Tip Three Lever Controls, Electric Joystick Steering, Rotating Beacon, Rear View Camera, 110 Volt Plug Heater, Auto Greasing System, Rubber Fender Protectors, Full Fender with Rubber Protector

NEW MODEL OVERVIEW	DL300-5
Rated Power – Gross (HP per SAE J1995)	271 hp (202 kW) @ 1,800 rpm
Operating Weight	41,844 lb. (18 980 kg)
Static Tipping Load (Straight)	33,907 lb. (15 380 kg)
Static Tipping Load (Full Turn)	29,939 lb. (13 580 kg)
Maximum Dumping Height	9' 4" (2845 mm)
Bucket Capacity Heaped	4.2 yd ³ (3.2 m ³)
Bucket Hinge Pin Height	13' (3975 mm)
Breakout Force	37,768 lbf. (17 131 kgf)
Maximum Dump (Reach @ full height)	3' 10" (1160 mm)
External Radius, Bucket Edge	21' (6405 mm)

PL-1006-0514

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net.