

# DOOSAN

# DL550-5 WHEEL LOADER

## NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- Standard Z-Bar (High Lift Z-Bar Available)
- Hydraulic Locking Front & Conventional Rear Differentials
- Selectable Work Modes (Eco, Normal & Power)
- Separate Cooling and Engine Compartments, Variable Speed Reversing Cooling Fan, Exhaust Heat Exchanger
- Telematics — 3 Year Subscription
- Options — Axle Oil Cooler, Emergency Steer, 5 Gear with Lock-up Clutch, Hydraulic Load Isolation System, Finger Tip Three Lever Controls, Electric Joystick Steering, Rotating Beacon, Rear View Camera, 110 Volt Plug Heater, Auto Greasing System, Rubber Fender Protectors, Full Fender with Rubber Protector

NEW MODEL OVERVIEW	DL550-5
Rated Power – Gross (HP per SAE J1995)	380 hp (283 kW) @ 1800 rpm
Operating Weight	69,909 lb. (31 710 kg)
Static Tipping Load (Straight)	54,432 lb. (24 690 kg)
Static Tipping Load (Full Turn)	48,061 lb. (21 800 kg)
Maximum Dumping Height	11' 2" (3405 mm)
Bucket Capacity Heaped	7.5 yd <sup>3</sup> (5.7 m <sup>3</sup> )
Bucket Hinge Pin Height	15' 9" (4795 mm)
Breakout Force	55,303 lbf. (25 085 kgf)
Maximum Dump (Reach @ full height)	4' 7" (1400 mm)
External Radius, Bucket Edge	24' 8" (7515 mm)

PL-1010-0414

# DOOSAN DELIVERS

*equipment for tough jobs*

\*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DL550-3.