

## Quick Couplers for Excavators

Approved for:	Model	Pin Diameter mm	Pin Centers (x-y) in (mm)	Weight in (kg)
DX55W	QC45H1G2	45	8.6 - 10.5 (218-267)	143 (65)
DX60R	QC45H1G2	45	8.6 - 10.5 (218-267)	143 (65)
DX80R	QC45H2G2	45	10.3 - 12.2 (262-311)	143 (65)
DX140	QC65H1G2	65	13.9 - 16.9 (355-430)	404 (183)
DX140LCR	QC65H1G2	65	13.9 - 16.9 (355-430)	404 (183)
DX140W	QC65H1G2	65	13.9 - 16.9 (355-430)	404 (183)
DX180LC	QC80H1G2	80	15.2 - 19.7 (385-500)	721 (327)
DX190W	QC80H1G2	80	15.2 - 19.7 (385-500)	721 (327)
DX210W	QC80H1G2	80	15.2 - 19.7 (385-500)	721 (327)
DX225LC	QC80H1G2	80	15.2 - 19.7 (385-500)	721 (327)
DX235LCR	QC80H1G2	80	15.2 - 19.7 (385-500)	721 (327)
DX255LC	QC80H1G2	80	15.2 - 19.7 (385-500)	721 (327)
DX300LC	QH90H-AL-B	90	18.7 - 22.2 (475-565)	961 (436)
DX350LC	QH100H0-B	100	20.9 - 24.8 (530-630)	1590 (721)
DX420LC	QH110H0-B	110	21.1 - 24.2 (535-615)	1640 (744)
DX480LC	QH120H0-B	120	22.4 - 25.0 (570-635)	2403 (1150)
DX520LC	QH120H0-B	120	22.4 - 25.0 (570-635)	2403 (1150)