

Ditching Buckets for Excavators

Approved Carriers	Width in (mm)	Operating Weight lbs (kg)	ISO Heaped Capacity cu yd (cu m)	Predrilled for
DX140	48.0 (1,219.2)	602 (273)	0.64 (0.49)	Cutting Edges
DX140	60.0 (1,524.0)	908 (412)	0.81 (0.62)	Cutting Edges
DX140	72.0 (1,828.8)	1,047 (475)	0.98 (0.75)	Cutting Edges
DX180, DX190W	48.0 (1,219.2)	602 (273)	0.64 (0.49)	Cutting Edges
DX180, DX190W	60.0 (1,524.0)	908 (412)	0.81 (0.62)	Cutting Edges
DX180, DX190W	72.0 (1,828.8)	1,047 (475)	0.98 (0.75)	Cutting Edges
DX210W, DX225, DX255	48.0 (1,219.2)	903 (410)	0.78 (0.60)	Cutting Edges
DX210W, DX225, DX255	60.0 (1,524.0)	1,307 (593)	0.98 (0.75)	Cutting Edges
DX210W, DX225, DX255	72.0 (1,828.8)	1,499 (680)	1.19 (0.91)	Cutting Edges
DX300	60.0 (1,524.0)	1,798 (816)	1.26 (0.96)	Cutting Edges
DX300	72.0 (1,828.8)	1,951 (885)	1.54 (1.18)	Cutting Edges
DX300	84.0 (2,133.6)	2,369 (1,075)	1.82 (1.39)	Cutting Edges
DX350	72.0 (1,828.8)	2,125 (964)	1.54 (1.18)	Cutting Edges
DX350	84.0 (2,133.6)	2,480 (1,125)	1.74 (1.33)	Cutting Edges
DX420	84.0 (2,133.6)	2,486 (1,128)	2.05 (1.57)	Cutting Edges
DX420	96.0 (2,438.4)	2,762 (1,253)	2.37 (1.81)	Cutting Edges